




# Introducing

# LongLine Crimp Sheets



#### **Material Specification**

**Standard Thickness (mm) -** 0.45 / 0.50 / 0.60


| Overall Length* |      | Option '1' (1 feet)      |                     | Option '2' (1.5 feet)    |                     |
|-----------------|------|--------------------------|---------------------|--------------------------|---------------------|
| (feet)          | (mm) | Long Line<br>Length (mm) | Crimp Curve<br>(mm) | Long Line<br>Length (mm) | Crimp Curve<br>(mm) |
| 8'              | 2440 | 2167                     | 305                 | 1971                     | 750                 |
| 10'             | 3050 | 2777                     | 305                 | 2581                     | 750                 |
| 12'             | 3660 | 3387                     | 305                 | 3191                     | 750                 |
| 14'             | 4270 | 3997                     | 305                 | 3801                     | 750                 |
| 16'             | 4880 | 4607                     | 305                 | 4411                     | 750                 |
| 18'             | 5490 | 5217                     | 305                 | 5021                     | 750                 |
| 20'             | 6100 | 5827                     | 305                 | 5631                     | 750                 |


# Benefits:


- ▶ No gutter required
  - Single length in standard sheet

## **DURASHINE® LongLine Crimp Sheets**


### **Typical Applications**








#### **Typical Sheet Arrangement**







Double slope roof with plan ridge



Crimp ridge





#### **Guard Film**

DURASHINE® LongLine Crimp Sheets come with the added protection of the Guard Film. The film not only adds protection to the sheet during storage, handling and installation but also enables the customer to identify the DURSHINE® brand

The guard film should be removed immediately on installation



#### **Disclaimer on Condensation:**

Condensation is the natural formation of water droplets on the bottom side of any installed metal roofing sheet. It may occur whenthere is a difference in temperature between the air in the building and the sheet itself, causing the water vapour (moisture) in the air to condense on the inside of the sheet. It is a natural phenomenon and hence no claims will be entertained in this regard.

The risk of condensation may be minimised by providing proper ventilation arrangement in the roofs and by using suitable insulation.



Maintenance Recommendation: Clean and maintain your roof regularly to remove dust and dirt.

Available
Standard ►
Colours\*

Asian White™ Castle Red<sup>™</sup> Passion Red<sup>™</sup>

Cherry Red<sup>™</sup> Bright Green<sup>™</sup>

M

Pearl Green™ Cool Blue™ Nuvo Blue™

/O \_™

Graphite Grey<sup>™</sup>

Coffee Brown<sup>™</sup>

\*Disclaimer: 1) The above colours are only for illustrative purpose and actual colours may vary. 2) All the above colour names are trademarks under DURASHINE® brand.



Dealer Name and Address

Download DURASHINE® APP





Email: durashine@tatabluescopesteel.com Website: www.tatabluescopesteel.com